

www.AVLELEC.com ww.ENTRAPASS.com www.TURNSTILES.us 8641 S. Warhawk Rd, Conifer, CO 80433 303-670-1099

pg. 1/2



### Model No.

# **LPOR2-1619**

# **Pull-out rack for built-in applications**

- 16U x 19.22"D x 19.06"W
- Two rail slides in base support 125 lbs.

Designed for built-in wall and millwork applications, the LPOR Series rack features heavy duty bottom rails to provide smooth, pull-out access to equipment and cables. The base installs with screws and can be mounted flush or recessed (up to 2") in a boxed wall or cabinetry.

#### **Construction & Features**

- Versatile low-cost racking solution for built-in applications
- 11-gauge steel corner post mounting rails (tapped 10-32). Front rails are 16U, rear rails are 7U.
- 14-ga. steel base with two bottom rails supports up to 125 lbs
- Side stiffeners assist torsional rigidity
- Three cable lacing bars facilitate organized cables
- Perforated front panel (typically mounted at top of rails)
- Perforated front secuirty panel screws into position to deter unauthorized access to mounted equipment
- · Black powder epoxy finish
- · Made in the USA with certified US steel
- Ships unassembled (two cartons)

## A&E Specifications

The rack for built-in use shall be AVLELEC Model No. LPOR2-1619 which shall measure 19.06"W x 19.22"D x 29.87"H and provide 16 rack units of panel space (16U front rails, 7U rear rails). The rack shall be made with certified U.S. steel and feature a 14-gauge steel base and 11-gauge steel mounting rails tapped 10-32. The base shall feature two heavy duty rails which shall allow the rack to slide forward while supporting a load up to 125 lbs. The rack shall include three cable lacing bars in the rear, two side stiffeners, a front vent panel and a front security panel which shall mount with screws to deter slide-out access to equip-ment as needed for security. The rack shall have a black powder epoxy finish and ship unassembled in two cartons.





All measurements are inches.







