



# Model No. UL-P68X Recessed backbox

Steel backbox for recessed installation in a ceiling or wall measures 10" square x 4" deep. Corners have a recessed mounting tab with 8-32 screw retaining U-clip (clip position assures protection and easy accessibility in plaster or poured concrete applications).

## Construction & Features

- Welded 18-gauge unitized steel
- 10" Sq x 4"D (0.231 cu.ft. volume)
- 1/2" - 3/4" combination knockouts for conduit
- Undercoated and lined with a foam pad to eliminate acoustic/mechanical resonance.
- Black powder epoxy finish.
- Made in the U.S.A. with certified U.S. steel
- Backbox is UL Listed only when used with speaker/grille assembly Model No. ULD-SG8-2T572 or No. ULS-SG8-CT572. It does not include rail mounting slots to accommodate SS Series rails; they must be screwed to the outside (order rails and screws separately).



**cULus**  
 UL Listed when used with  
 speaker/grille assembly  
 Model No. ULD-SG8-2T572  
 or ULS-SG8-CT572

## A & E Specifications

The UL Listed backbox for recessed installation of speaker/grille assembly Model No. \_\_\_\_\_ (ULD-SG8-2T572 or ULS-SG8-CT572, ordered separately) shall be AVLELEC Model No. UL-P68X, which shall measure 10" Sq. x 4"D and have a volume of 0.231 cu.ft. It shall be formed from 18-gauge steel, welded and finished in black powder epoxy paint. It shall be undercoated and lined with a foam pad. The backbox shall feature 1/2" - 3/4" knockouts for conduit on four sides and shall include recessed mounting tabs with 8-32 U-clips.

## Compatible Components (order separately)

- Speaker/Grille Assemblies.....ULD-SG8-2T572  
 ULS-SG8-CT572

## Model Number

Product No.	Description	Dimensions	Volume (cu.ft.)	Lining
UL-P68X	Recessed steel backbox for use with 8" speaker	10" x 10" x 4"	0.231	foam pad

### Technical Drawings

